



### Construction

Fixture body made out of carbon fiber, matte black finish.

### LEDs

50,000-hour rated life; available in 3200°K or 5600°K; power draw 50-watts with 0-100 dimming and sensor to detect LED temperature.

### Fresnel Lens

Lupolux 650 lens is 120-mm.

### Control

DMX-512 0-100% dimming in and out with standard XLR 5-pin connectors; on-board manual dimming 0-100%; and 4-pin connection for battery operation.

### Power

Extremely low power consumption (50-watt) and high light efficiency (equivalent to 500-watt tungsten), 90V to 240V; 50-watt power draw.

### Accessories

Yoke, c-clamp and barn doors included, TV-MP adapter available as option.

### Dimensions

Lupolux 650 fixture is 7.48- x 6.49- x 7.08-in (190.00- x 164.85- x 179.83-mm).

### Fixture Weight

Lupolux 650 fixture is 5.5-lb (2.5-kg).

### Electrical Certifications

CE Certified.

580 Mayer Street - Building # 7 - Bridgeville, PA 15017 USA

Phone: 1.412.206.0106 - Fax: 1.412.206.0146



**brightline**<sup>®</sup>

© 2016 Brightline LP All Rights Reserved



**Photometrics**

**Distance From Subject**

	3-ft 0.91-m	7-ft 2.13-m	10-ft 3.05-m	16-ft 4.87-m	33-ft 10.05-m
--	----------------	----------------	-----------------	-----------------	------------------

**Spot Focus**

Footcandles on Center (3200°K)	1579	381	130	57	19
Footcandles on Center (5600°K)	1858	474	139	93	23

**Flood Focus**

Footcandles on Center (3200°K)	372	70	37	19	8
Footcandles on Center (5600°K)	418	72	48	20	8

**Fixture Options**

<b>Color Temperature</b>	<b>Part Number</b>
3200K	<b>LL650-32</b>
5600K	<b>LL650-56</b>

580 Mayer Street - Building # 7 - Bridgeville, PA 15017 USA

Phone: 1.412.206.0106 - Fax: 1.412.206.0146



© 2016 Brightline LP All Rights Reserved