

### **LED Personal Video Light**



The i-Series, a sleek energy-efficient LED fixture, is scalable to virtually any monitor. Cool-to-the-touch, the i-Series fixtures make it easy to look your best on camera, allowing individuals to conference remotely without sacrificing critical visual details.

The many non-verbal nuances of facial expression and eye contact are critical to effective communications. The i-Series enhances visual clarity, thereby increasing the readable content with a video image and raising the engagement level of participants in conference.

## Model Number

22 inch	i-S/22
Clamp Mount	i-S/CM



# **Specifications**

#### Construction

.078-in thick aluminum extruded housing. Aluminum cast end caps, .09-in aluminum reflector powder coated gloss white, a smooth gloss black powder-coated finish (SW-PBS8-COOO-C50) is standard, with custom colors available by request.

#### **Electrical**

6-ft (1.8-m) power cord with built-in low voltage transformer connects to fixture housing using single pin connector. Plug is a NEMA 5-15P and is standard for 120V fixtures; 230V plug options are avaliable upon request. Inline rotary dimming transformer is standard. High-power LED strips mounted on reflector. 20-watt power draw.

#### Mounting

The Mini Clamp mounting brackets include a 27-in gooseneck and are sold separately.

#### **Louver and Lens**

Fixtures are provided with .50-in x .50-in black egg crate louver and LED film.

#### **Dimensions**

The fixture has dimensions of 1.7-in (43.43-mm) x 3.5-in (88.9-mm) deep x 22.4-in (569.21-mm) long.



580 Mayer Street - Building # 7 - Bridgeville, PA 15017 USA

