



brightline
Evolutionary Lighting Systems

Lupolux 2000 by Brightline

LED Studio Fixture



Construction

Fixture body made out of carbon fiber, matte black finish.

LEDs

50,000-hour rated life; available in 3200°K or 5600°K; power draw 90-watts with 0-100 dimming and sensor to detect LED temperature.

Fresnel Lens

Lupolux 2000 fixture lens is 200-mm.

Control

DMX-512 0-100% dimming in and out with standard XLR 5-pin connectors; on-board manual dimming 0-100%; and 4-pin connection for battery operation.

Power

Low power consumption (220-watt) and high light efficiency (equivalent to 2000-watt tungsten), 90V to 240V; 220-watt power draw.

Accessories

Yoke, c-clamp and barn doors included, TV-MP adapter available as option.

Dimensions

Lupolux 1000 fixture is 11.81- x 10.24- x 9.84-in (300.00- x 260.00- x 250.00-mm).

Fixture Weight

Lupolux 1000 fixture is 10.6-lb (4.8-kg).

Electrical Certifications

CE

580 Mayer Street - Building # 7 - Bridgeville, PA 15017 USA

Phone: 1.412.206.0106 - Fax: 1.412.206.0146



© 2016 Brightline LP All Rights Reserved



Photometrics	Distance From Subject				
	3-ft 0.91-m	7-ft 2.13-m	10-ft 3.05-m	16-ft 4.87-m	20-ft 6.10m
Spot Focus					
Footcandles on Center (5600°K)	6630	1770	800	271	190
Flood Focus					
Footcandles on Center (5600°K)	1541	383	170	61	42

Fixture Options

Color Temperature	Part Number
3200K	LL2000-32
5600K	LL2000-56

580 Mayer Street - Building # 7 - Bridgeville, PA 15017 USA

Phone: 1.412.206.0106 - Fax: 1.412.206.0146



© 2016 Brightline LP All Rights Reserved

Specifications are subject to change without notice.

12/06/16