



Construction

Fixture body made out of carbon fiber, matte black finish.

LEDs

50,000-hour rated life; available in 3200°K or 5600°K, Variable Color available in Lupo 650 and Lupo 1000 models; power draw 60-, 110- or 220-watts with 0-100 dimming and sensor to detect LED temperature.

Fresnel Lens

Lupolux 650 lens is 4.7-in (120-mm).
Lupolux 1000 fixture lens is 5.9-in (150-mm).
Lupolux 2000 fixture lens is 7.9-in (200-mm).

Control

DMX-512 0-100% dimming in and out with standard XLR 5-pin connectors; on-board manual dimming 0-100%; and 4-pin connection for battery operation.

Power

Extremely low power consumption (60-, 110- or 220-watt) and high light efficiency (equivalent to 650-, 1000- or 2000-watt tungsten), 90V to 240V; 60-, 110- or 220-watt power draw.

Accessories

Yoke, c-clamp and barn doors included, TV-MP adapter available as stand mount option.

Electrical Certifications

CE



Dimensions

Lupo 650: 7.48- x 6.49- x 7.08-in
(190.00- x 164.85- x 179.83-mm)

Lupo 1000: 8.27- x 10.24- x 9.05-in
(210.05- x 260.10- x 230.00-mm)

Lupo 2000: 11.81- x 10.24- x 9.84-in
(300.00- x 260.00- x 250.00-mm).

Fixture Weight

Lupo 650: 5.5-lb (2.5-kg)
Lupo 1000: 6.6-lb (3.0-kg)
Lupo 2000: 10.6-lb (4.8-kg)

Photometrics		Distance From Subject					
Footcandles on Center	CCT	3-ft 0.91-m	7-ft 2.13-m	10-ft 3.05-m	16-ft 4.87-m	20-ft 6.10-m	33-ft 10.05-m
LL650 Spot Focus	3200°K	1579	381	130	57	N/A	19
	5600°K	1858	474	139	93	N/A	23
LL650 Flood Focus	3200°K	372	70	37	19	N/A	8
	5600°K	418	72	48	20	N/A	8
LL1000 Spot Focus	3200°K	2881	929	325	130	N/A	28
	5600°K	4088	1208	557	172	N/A	41
LL1000 Flood Focus	3200°K	557	130	51	20	N/A	9
	5600°K	929	177	65	29	N/A	10
LL2000 - Spot Focus	5600°K	6630	1770	800	271	190	N/A
LL2000 - Flood Focus	5600°K	1541	383	170	61	42	N/A



Lupo DayLED Fresnel Fixtures



Part Number	Fixture Description
LL650-32-CM	Lupo DayLED 650, 3200°K, Clamp Mount
LL650-32-SM	Lupo DayLED 650, 3200°K, Stand Mount
LL650-56-CM	Lupo DayLED 650, 5600°K, Clamp Mount
LL650-56-SM	Lupo DayLED 650, 5600°K, Stand Mount
LL650-VC-CM	Lupo DayLED 650, Variable Color, Clamp Mount
LL650-VC-SM	Lupo DayLED 650, Variable Color, Stand Mount
LL1000-32-CM	Lupo DayLED 1000, 3200°K, Clamp Mount
LL1000-32-SM	Lupo DayLED 1000, 3200°K, Stand Mount
LL1000-56-CM	Lupo DayLED 1000, 5600°K, Clamp Mount
LL1000-56-SM	Lupo DayLED 1000, 5600°K, Stand Mount
LL1000-VC-CM	Lupo DayLED 1000, Variable Color, Clamp Mount
LL1000-VC-SM	Lupo DayLED 1000, Variable Color, Stand Mount
LL2000-32-CM	Lupo DayLED 2000, 3200°K, Clamp Mount
LL2000-32-SM	Lupo DayLED 2000, 3200°K, Stand Mount
LL2000-56-CM	Lupo DayLED 2000, 5600°K, Clamp Mount
LL2000-56-SM	Lupo DayLED 2000, 5600°K, Stand Mount

Lupolux DayLED Fixture Accessories

Part Number	Accessory Description
LL-V-MNT-ADPT-PLT-ASSY	V-Mount Adapter Plate (Includes Plate and 2-Pin D-Tap Power Cable)
LL-BAT-PACK-BAGS-YOKE-MNT-2000	Battery Pack Bags for Yoke Mounting
LL-V-MNT-BAT-1HR	1-Hour V-Mount Battery
LL-V-MNT-BAT-CHRGR	V-Mount Battery Charger
LL-PDD-BAG	Bag Padded

