



Construction

Fixture body made out of carbon fiber, matte black finish.

LEDs

50,000-hour rated life; available in 3200°K or 5600°K, Variable Color available in Lupo 650 and Lupo 1000 models; power draw 60-, 110- or 220-watts with 0-100 dimming and sensor to detect LED temperature.

Fresnel Lens

Lupolux 650 lens is 4.7-in (120-mm).

Lupolux 1000 fixture lens is 5.9-in (150-mm).

Lupolux 2000 fixture lens is 7.9-in (200-mm).

Control

DMX-512 0-100% dimming in and out with standard XLR 5-pin connectors; on-board manual dimming 0-100%; and 4-pin connection for battery operation.

Power

Extremely low power consumption (60-, 110- or 220-watt) and high light efficiency (equivalent to 650-, 1000- or 2000-watt tungsten), 90V to 240V; 60-, 110- or 220-watt power draw.

Accessories

Yoke, c-clamp and barn doors included, TV-MP adapter available as stand mount option.

Certifications

CE

Dimensions

Lupo 650: 7.48- x 6.49- x 7.08-in
(190.00- x 164.85- x 179.83-mm)

Lupo 1000: 8.27- x 10.24- x 9.05-in
(210.05- x 260.10- x 230.00-mm)

Lupo 2000: 11.81- x 10.24- x 9.84-in
(300.00- x 260.00- x 250.00-mm).

Fixture Weight

Lupo 650: 5.5-lb (2.5-kg)

Lupo 1000: 6.6-lb (3.0-kg)

Lupo 2000: 10.6-lb (4.8-kg)

See shipping information chart for gross weights and dimensions.

Photometrics

Distance From Subject

Footcandles on Center

CCT

3-ft
0.91-m

7-ft
2.13-m

10-ft
3.05-m

16-ft
4.87-m

20-ft
6.10-m

33-ft
10.05-m

LL650
Spot Focus

3200°K

1579

381

130

57

N/A

19

5600°K

1858

474

139

93

N/A

23

LL650
Flood Focus

3200°K

372

70

37

19

N/A

8

5600°K

418

72

48

20

N/A

8

LL1000
Spot Focus

3200°K

2881

929

325

130

N/A

28

5600°K

4088

1208

557

172

N/A

41

LL1000
Flood Focus

3200°K

557

130

51

20

N/A

9

5600°K

929

177

65

29

N/A

10

LL2000 - Spot Focus

5600°K

6630

1770

800

271

190

N/A

LL2000 - Flood Focus

5600°K

1541

383

170

61

42

N/A





Lupo DayLED Fresnel Fixtures



| Part Number | Fixture Description |
|--------------|---|
| LL650-32-CM | Lupo DayLED 650, 3200°K, Clamp Mount |
| LL650-32-SM | Lupo DayLED 650, 3200°K, Stand Mount |
| LL650-56-CM | Lupo DayLED 650, 5600°K, Clamp Mount |
| LL650-56-SM | Lupo DayLED 650, 5600°K, Stand Mount |
| LL650-VC-CM | Lupo DayLED 650, Variable Color, Clamp Mount |
| LL650-VC-SM | Lupo DayLED 650, Variable Color, Stand Mount |
| LL1000-32-CM | Lupo DayLED 1000, 3200°K, Clamp Mount |
| LL1000-32-SM | Lupo DayLED 1000, 3200°K, Stand Mount |
| LL1000-56-CM | Lupo DayLED 1000, 5600°K, Clamp Mount |
| LL1000-56-SM | Lupo DayLED 1000, 5600°K, Stand Mount |
| LL1000-VC-CM | Lupo DayLED 1000, Variable Color, Clamp Mount |
| LL1000-VC-SM | Lupo DayLED 1000, Variable Color, Stand Mount |
| LL2000-32-CM | Lupo DayLED 2000, 3200°K, Clamp Mount |
| LL2000-32-SM | Lupo DayLED 2000, 3200°K, Stand Mount |
| LL2000-56-CM | Lupo DayLED 2000, 5600°K, Clamp Mount |
| LL2000-56-SM | Lupo DayLED 2000, 5600°K, Stand Mount |

Lupolux DayLED Fixture Accessories

| Part Number | Accessory Description |
|--------------------------------|--|
| LL-V-MNT-ADPT-PLT-ASSY | V-Mount Adapter Plate (Includes Plate and 2-Pin D-Tap Power Cable) |
| LL-BAT-PACK-BAGS-YOKE-MNT-2000 | Battery Pack Bags for Yoke Mounting |
| LL-V-MNT-BAT-1HR | 1-Hour V-Mount Battery |
| LL-V-MNT-BAT-CHRGR | V-Mount Battery Charger |
| LL-PDD-BAG | Bag Padded |



580 Mayer Street - Building # 7 - Bridgeville, PA 15017 USA

Phone: 1.412.206.0106

www.brightlines.com



© 2019 Brightline LP All Rights Reserved

Specifications are subject to change without notice.

03/09/20