

LED VideoPlus Indirect (LVCI)

Exceptional Indirect LED Video Lighting



LED VideoPlus Indirect (LVCI)

Exceptional Indirect LED Video Lighting

Construction

Fixture housing is made of formed, cold-rolled sheet steel.

Fixture Body Finish

Low-gloss Signal White finish (Ral #9003, 20% Gloss) is standard, with custom colors available.

Low Voltage Control

19" Rack-mounted driver is available with up to 600w of power. Multiple drivers can be linked for any size project. Low voltage control available for 120-230V applications.

Power Over Ethernet Control

Fixtures are available with PoE control nodes. Consult with factory for specification of complete PoE systems. PoE Control available for 120-230V applications.

LED Technology

The fixture utilizes mid-power LEDs with high-quality illumination (>97 CRI) for videoconferencing and general lighting applications. Each fixture module has a power consumption of 44 watts.


Drivers

All drivers are high-frequency electronic, with a power factor > .90, THD < 20%, and a Class A sound rating. Drivers are mounted internally.

Reflector

Reflector is formed aluminum White-Optics sheet-metal construction, featuring 95% reflectance.

Dimming Protocol	Voltage
A = 0-10V	1 = 120V
E = Lutron LDE1	2 = 230V
X = DALi	7= 277V
L = Low Voltage	U = L or Z Dimming only
Z = PoE (60W)*	
	A = 0-10V E = Lutron LDE1 X = DALi L = Low Voltage






Mounting


Fixture can be mounted in a suspended, lay-in grid ceiling. Optional drywall frame kit available.

2-ft x 2-ft: 23.75- x 23.75- x 7.08-in (603.25- x 603.25- x 179.62-mm)

Fixture Weight: 22-lb (10-kg)

See shipping information chart for gross weights and dimension.





NOTE: Variable White (VW) available on DALI and DMX fixtures only

*Consult factory to ensure PoE system compatibility

580 Mayer Street, Building #7, Bridgeville, PA 15017, USA Brightlines.com | 1.412.206.0106