



Lupo DayLED Pro by Brightline
60-, 110- or 220-watt LED Fresnel

Construction

Fixture body made out of carbon fiber, matte black finish.

LEDs

50,000-hour rated life; available in 3200°K or 5600°K, or Variable White; power draw 60-, 110- or 220-watts with 0-100 dimming and sensor to detect LED temperature.

Fresnel Lens

Lupolux 650 Pro fixture lens is 4.7-in (120-mm). Lupolux 1000 Pro fixture lens is 5.9-in (150-mm). Lupolux 2000 Pro fixture lens is 7.9-in (200-mm).

Control

DMX-512 0-100% dimming in and out with standard XLR 5-pin connectors; on-board manual dimming 0-100%; and 4-pin connection for battery operation. RDM enabled.

Power

Extremely low power consumption (60-, 110- or 220-watt) and high light efficiency (equivalent to 650-, 1000- or 2000-watt tungsten), 90V to 240V; 60-, 110- or 220-watt power draw. Power Con in and out. 9.8-ft (3-m) Power Con to edison included.

Accessories

Yoke, c-clamp and barndoors included. TV-MP adapter available as stand mount option.



Certifications

CE

Dimensions

Lupo 650 Pro: 10.6- x 11.0- x 11.0-in
(270.0- x 280.0- x 280.0-mm)

Lupo 1000 Pro: 10.6- x 11.0- x 11.8-in
(270.0- x 280.0- x 300.00-mm)

Lupo 2000 Pro: 10.6- x 12.0- x 13.0-in
(270.0- x 310.0- x 330.0-mm).

Fixture Weight

Lupo 650 Pro: 5.5-lb (2.5-kg)

Lupo 1000 Pro: 6.6-lb (3.0-kg)

Lupo 2000 Pro: 10.6-lb (4.8-kg)

See shipping information chart for gross weights and dimensions.

Photometrics

Distance From Subject

Footcandles on Center	CCT	Distance From Subject						
		3-ft 0.91-m	7-ft 2.13-m	10-ft 3.05-m	16-ft 4.87-m	20-ft 6.10-m	33-ft 10.05-m	
LL650 Pro	3200°K	1579	381	130	57	N/A	19	
Spot Focus	5600°K	1858	474	139	93	N/A	23	
LL650 Pro	3200°K	372	70	37	19	N/A	8	
Flood Focus	5600°K	418	72	48	20	N/A	8	
LL1000 Pro	3200°K	2881	929	325	130	N/A	28	
Spot Focus	5600°K	4088	1208	557	172	N/A	41	
LL1000 Pro	3200°K	557	130	51	20	N/A	9	
Flood Focus	5600°K	929	177	65	29	N/A	10	
LL2000 Pro Spot Focus	5600°K	6630	1770	800	271	190	N/A	
LL2000 Pro Flood Focus	5600°K	1541	383	170	61	42	N/A	



Lupo DayLED Fresnel Fixtures

Part Number	Fixture Description
LL650-VC-CM	Lupo DayLED 650 Pro, Variable Color, Clamp Mount
LL650-VC-SM	Lupo DayLED 650 Pro, Variable Color, Stand Mount
LL1000-VC-CM	Lupo DayLED 1000 Pro, Variable Color, Clamp Mount
LL1000-VC-SM	Lupo DayLED 1000 Pro, Variable Color, Stand Mount
LL2000-VC-CM	Lupo DayLED 2000 Pro, Variable Color, Clamp Mount
LL2000-VC-SM	Lupo DayLED 2000 Pro, Variable Color, Stand Mount

Lupolux DayLED Fixture Accessories

Part Number	Accessory Description
LL-V-MNT-ADPT-PLT-ASSY	V-Mount Adapter Plate (Includes Plate and 2-Pin D-Tap Power Cable)
LL-BAT-PACK-BAGS-YOKE-MNT-2000	Battery Pack Bags for Yoke Mounting
LL-V-MNT-BAT-1HR	1-Hour V-Mount Battery
LL-V-MNT-BAT-CHRGR	V-Mount Battery Charger
LL-PDD-BAG	Bag Padded

