



Product Description: Remote power driver, 600W, DMX control, up to 32 channels, constant current, 32 x 48V outputs, 1U 19-in rack

Input Characteristics:

Nominal 120 -230V (UL), 6.3A at 120V/60Hz or 5A at 230V/50Hz maximum current, input frequency of 50-60Hz, power factor >0.90, THD at full load is <20%, 91.8% efficient at full load

Output Characteristics

Maximum LED output power is 600W, 32 LED outputs, 200-1050mA programmable current range in 50mA steps via display, LED output range is 2-48V

Control Characteristics

Up to 32 DMX channels, .01%-100% dimming, three dimming curves: logarithmic (default), linear or square, connectors for each channel provided by Brightline

Weights and Dimensions

19.0- x 12.8- x 1.75-in (482.6- x 325.0- x 44.5-mm)
13.9-lb (6.3kg)
1U - 19-in (482.6-mm) rack



Certifications & Warranty

- CE Directives 2004/108/EC, 2006/95/EC, EN 60929 Annex E
- UL Listed
- 3 year limited warranty

Part Number Configurations:

CTRL-RPD-LV-6060-FLXT for Flex-T or VideoPlus
CTRL-RPD-LV-6060-LST6 for Stealth-T
CTRL-RPD-LV-6060-BL16 for BL.16
CTRL-RPD-LV-6060-LVCI for LVCI